

# PRIMO D M2 302 M DATA2 B TM-PD.M2BDM300B

Click on the selected icon to download the file:



No: 0525



No: 4672/2022  
Valid until:  
13.06.2027



No: 88-128507



No:  
B\_BK\_60112\_0428\_2024  
Valid until:  
24.01.2030



No: 0525



No: DC-UAE-  
0214  
Valid until:  
13.06.2027



No: 0525




No: V1



No: V1.5



Producer	<b>TM Technologie</b>
Application	<b>anti-panic lighting</b>
Family	<b>PRIMO D</b>
Colour/Colour - RAL	<b>black , RAL9005</b>
Version	<b>DATA2</b>
Operating mode	<b>M</b>
Duration time	<b>3 h</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK03</b>
Appliance classes	<b>I</b>
Material	<b>steel</b>
Installation method*	<b>flush-mounted, ceiling</b>
Luminous flux	<b>- cd/m<sup>2</sup></b>
Luminous flux emergency	<b>224 lm</b>
Light source	<b>LED</b>
Maximum light power	<b>3 W</b>
Active power	<b>7 W</b>
Nominal voltage AC	<b>210-250 V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>+10 °C</b>
Maximum temperature	<b>+35 °C</b>
Battery	<b>LiFePO4/C (LN) 6.4V 1.5-1.6Ah</b>
Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>90 mm x 90 mm x 13 mm</b>



\* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	3,5	7,5	3,5	7,5
3	3,5	8,5	3,5	8,5
4	4	10,5	4	10,5
5	5	12	5	12
6	5	14	5	14
7	5	15	5	15
8	4,5	16	4,5	16
9	3	17	3	17
10	4	16	4	16

$E_{min} \geq 0,5 \text{ lx}$