

# PRIMO E 30E 01 CB W TM-PE.3ECB0000W

Click on the selected icon to download the file:



No: 0625



No: 4599/2022  
Valid until:  
20.03.2027



No: 88-141849  
Valid until:  
28.02.2027



No:  
B\_BK\_60112\_0429\_2024  
Valid until:  
24.01.2030



No: 0625



No: DC-UAE-0204  
Valid until:  
20.03.2027



No: 0625



No: V1.9



Producer	<b>TM Technologie</b>
Category	<b>emergency luminaires</b>
Application	<b>evacuation route direction</b>
Family	<b>PRIMO E</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Colour structure	<b>painted</b>
Version	<b>CB - central battery</b>
Operating mode	<b>CB</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK05</b>
Appliance classes	<b>I</b>
Material	<b>steel</b>
Installation method*	<b>surface, flush-mounted, wall</b>
Adapted to use a pictogram	<b>yes</b>
Pictogram included	<b>yes</b>
Pictogram dimensions	<b>317x179 mm</b>
Evacuation sign dimensions	<b>300x150 mm</b>
Pictogram type	<b>foil</b>
Graphic number	<b>K3</b>
Luminous flux	<b>&gt;250 cd/m<sup>2</sup></b>
Visibility	<b>30 m</b>
Colour temperature	<b>5700 K</b>
Nominal voltage AC	<b>210-250 V</b>
Nominal voltage DC	<b>186-254 V</b>
Light source	<b>LED</b>
Maximum light power	<b>1.5 W</b>
LED lifetime	<b>50000 h</b>
Minimum temperature	<b>-15 °C</b>
Maximum temperature	<b>+55 °C</b>

Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>322 mm x 39 mm x 184 mm</b>

