
# PRIMO E 60E 02 CB B
# TM-PE.6ECB0000B

Click on the selected icon to download the file:

No: 0626 | No: 4599/2022 Valid until: 20.03.2027 | No: 88-141849 Valid until: 31.12.2027 | No: B_BK_60112_0429_2024 Valid until: 24.01.2030 | No: 0626 | No: DC-UAE-0204 Valid until: 20.03.2027 | No: 0626 | No: V1.10



| | |
|---|---|
| Producer | **TM TECHNOLOGIE** |
| Category | **emergency luminaires** |
| Application | **evacuation route direction** |
| Family | **PRIMO E** |
| Colour | **black** |
| Colour - RAL | **RAL9005** |
| Colour structure | **painted** |
| Version | **CB - central battery** |
| Operating mode | **CB** |
| Protection degree | **IP20** |
| Impact protection degree | **IK05** |
| Appliance classes | **I** |
| Material | **steel** |
| Installation method* | **surface, flush-mounted, wall** |
| Adapted to use a pictogram | **yes** |
| Pictogram dimensions | **617x329 mm** |
| Evacuation sign dimensions | **600x300 mm** |
| Pictogram type | **foil** |
| Luminous flux | **>200 cd/m²** |
| Visibility | **60 m** |
| Colour temperature | **5700 K** |
| Nominal voltage AC | **210-250 V** |
| Nominal voltage DC | **186-254 V** |
| Light source | **LED** |
| Maximum light power | **3.6 W** |
| Active power | **5.7 W** |
| LED lifetime | **50000 h** |
| Minimum temperature | **-15 °C** |
| Maximum temperature | **+55 °C** |
| Warranty (body, electronics, light source) | **60 months** |
| Net dimensions **L x W x H** [±2 mm] | **622 mm x 39 mm x 334 mm** |




* Some of mounting methods are possible only with additonal accessory dedicated for that product.