TM TECHNOLOGIE

PRIMO E 80E 180 M AT M
TM-PE.8EATM800M

Click on the selected icon to download the file:

No: 0626

No: 4599/2022
Valid until:
20.03.2027

No: 88-128526

No:
B_BK_60112_0429_2024
Valid until:
24.01.2030

No: 0626

No: DC-UAE-
0204
Valid until:
20.03.2027


No: 0626

No: DIT.V1.01

No: V1.10



Producer	**TM TECHNOLOGIE**
Category	**emergency luminaires**
Application	**evacuation route direction**
Family	**PRIMO E**
Colour	**mirror**
Colour structure	**gloss**
Version	**autotest**
Operating mode	**M**
Duration time	**3 h**
Protection degree	**IP20**
Impact protection degree	**IK05**
Appliance classes	**I**
Material	**stainless steel**
Installation method*	**surface, flush-mounted, wall**
Adapted to use a pictogram	**yes**
Pictogram dimensions	**817x429 mm**
Evacuation sign dimensions	**800x400 mm**
Pictogram type	**foil**
Luminous flux	**>150 cd/m²**
Visibility	**80 m**
Colour temperature	**5700 K**
Nominal voltage AC	**210-250 V**
Light source	**LED**
Maximum light power	**3 W**
Active power	**6.6 W**
LED lifetime	**50000 h**
Minimum temperature	**+10 °C**
Maximum temperature	**+35 °C**
Battery	**LiFePO4/C (LN) 3.2V 3.0-3.2Ah**
Warranty (body, electronics, light source)	**36 months**
Net dimensions **L x W x H** [±2 mm]	**822 mm x 39 mm x 434 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.