
PRIMO G 30E 01 CB B
TM-PG.3ECB0000B

Click on the selected icon to download the file:

No: 0726 | No: 4600/2022 Valid until: 21.03.2027 | No: 88-141985 Valid until: 31.12.2027 | No: B_BK_60112_0429_2024 Valid until: 24.01.2030 | No: 0726 | No: DC-UAE-0205 Valid until: 21.03.2027 | No: 0726 | No: V1.7



Producer	**TM TECHNOLOGIE**
Category	**emergency luminaires**
Application	**evacuation route direction**
Family	**PRIMO G**
Colour	**black**
Colour - RAL	**RAL9005**
Colour structure	**painted**
Version	**CB - central battery**
Operating mode	**CB**
Protection degree	**IP20**
Impact protection degree	**IK05**
Appliance classes	**I**
Material	**steel**
Installation method*	**surface, wall, ceiling**
Adapted to use a pictogram	**yes**
Pictogram included	**yes**
Pictogram dimensions	**150x150 mm**
Evacuation sign dimensions	**300x150 mm**
Pictogram type	**foil**
Graphic number	**K6**
Pictogram logo	**TM TECHNOLOGIE**
Luminous flux	**>250 cd/m²**
Visibility	**30 m**
Colour temperature	**5700 K**
Nominal voltage AC	**210-250 V**
Nominal voltage DC	**186-254 V**
Light source	**LED**
Maximum light power	**1 W**
Active power	**2.3 W**
LED lifetime	**50000 h**
Minimum temperature	**-15 °C**
Maximum temperature	**+55 °C**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **L x W x H** [±2 mm]	**301 mm x 30 mm x 219 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.