

PRIMO G 30E 301 M DALI B TM-PG.3EDAM300B

Click on the selected icon to download the file:



No: 0725



No: 4600/2022
Valid until:
21.03.2027



No: B_BK_60112_0429_2024
Valid until:
24.01.2030



No: 0725



No: DC-UAE-0205
Valid until:
21.03.2027



No: 3336



No: 0725



No: V1



No: V1.6



Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction
Family	PRIMO G
Colour/Colour - RAL	black , RAL9005
Colour structure	painted
Version	DALI
Operating mode	M
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK05
Appliance classes	I
Material	steel
Installation method*	surface, wall, ceiling
Adapted to use a pictogram	yes
Pictogram included	yes
Pictogram dimensions	150x150 mm
Evacuation sign dimensions	300x150 mm
Pictogram type	foil
Graphic number	K6
Pictogram logo	TM Technologie
Luminous flux	>250 cd/m²
Visibility	30 m
Colour temperature	5700 K
Nominal voltage AC	210-250 V
Light source	LED
Maximum light power	1 W
LED lifetime	50000 h
Minimum temperature	+10 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C (LN) 6.4V 1.5-1.6Ah
DALI type	B
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	301 mm x 30 mm x 219 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.