PRIMO G 30E 301 M DALI-2 W
TM-PG.3EDLM300W


Click on the selected icon to download the file:

No: 0726 | No: 4600/2022 Valid until: 21.03.2027 | No: B_BK_60112_0429_2024 Valid until: 24.01.2030 | No: 0726 | No: DC-UAE-0205 | No: 6999 | No: 0726 | No: DIT.V1.01

No: V1.7



Producer	**TM TECHNOLOGIE**
Category	**emergency luminaires**
Application	**evacuation route direction**
Family	**PRIMO G**
Colour	**white**
Colour - RAL	**RAL9003**
Colour structure	**painted**
Version	**DALI2**
Operating mode	**M**
Duration time	**3 h**
Protection degree	**IP20**
Impact protection degree	**IK05**
Appliance classes	**I**
Material	**steel**
Installation method*	**surface, wall, ceiling**
Adapted to use a pictogram	**yes**
Pictogram included	**yes**
Pictogram dimensions	**150x150 mm**
Evacuation sign dimensions	**300x150 mm**
Pictogram type	**foil**
Graphic number	**K6**
Pictogram logo	**TM TECHNOLOGIE**
Luminous flux	**>250 cd/m²**
Visibility	**30 m**
Colour temperature	**5700 K**
Nominal voltage AC	**210-250 V**
Nominal voltage DC	**- V**
Light source	**LED**
Maximum light power	**1 W**
Active power	**4.9 W**
LED lifetime	**50000 h**
Minimum temperature	**+10 °C**
Maximum temperature	**+35 °C**
Battery	**LiFePO4/C (LN) 6.4V 1.5-1.6Ah**
DALI type	**B**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **L x W x H** [±2 mm]	**301 mm x 30 mm x 219 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.