

PRIMO G 40E 01 CB W TM-PG.4ECB0000W

Click on the selected icon to download the file:



No: 0725



No: 4600/2022
Valid until:
21.03.2027



No: 88-141985
Valid until:
28.02.2027



No:
B_BK_60112_0429_2024
Valid until:
24.01.2030



No: 0725



No: DC-UAE-0205
Valid until:
21.03.2027




No: 0725



No: V1.6



Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction
Family	PRIMO G
Colour/Colour - RAL	white , RAL9003
Colour structure	painted
Version	CB - central battery
Operating mode	CB
Protection degree	IP20
Impact protection degree	IK05
Appliance classes	I
Material	steel
Installation method*	surface, wall, ceiling
Adapted to use a pictogram	yes
Pictogram included	yes
Pictogram dimensions	200x200 mm
Evacuation sign dimensions	400x200 mm
Pictogram type	foil
Graphic number	K6
Pictogram logo	TM Technologie
Luminous flux	>200 cd/m²
Visibility	40 m
Colour temperature	5700 K
Nominal voltage AC	210-250 V
Nominal voltage DC	186-254 V
Light source	LED
Maximum light power	1.5 W
LED lifetime	50000 h
Minimum temperature	-15 °C
Maximum temperature	+55 °C
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	401 mm x 30 mm x 269 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.