TM TECHNOLOGIE

# PRIMO PP 30D 180 M AT W
# TM-PP.30D.AT03W

Click on the selected icon to download the file:

No: 1726 | No: 6077/2026 Valid until: 19.05.2031 | No: B_BK_60112_0427_2024 Valid until: 24.01.2030 | No: 1726 | No: DC-UAE-0374 Valid until: 19.05.2031 | No: 1726 | No: DIT.V1.01 | No: V1.0

| | |
|---|---|
| Producer | **TM TECHNOLOGIE** |
| Category | **emergency luminaires** |
| Application | **evacuation route direction** |
| Family | **PRIMO PP** |
| Colour | **white** |
| Colour - RAL | **RAL9003** |
| Colour structure | **painted** |
| Version | **autotest** |
| Operating mode | **M** |
| Duration time | **3 h** |
| Protection degree | **IP20** |
| Impact protection degree | **IK07** |
| Appliance classes | **I** |
| Material | **steel** |
| Installation method* | **ceiling** |
| Adapted to use a pictogram | **yes** |
| Pictogram included | **yes** |
| Pictogram dimensions | **300x150 mm** |
| Evacuation sign dimensions | **300x150 mm** |
| Pictogram type | **sticker** |
| Graphic number | **K3** |
| Luminous flux | **>500 cd/m²** |
| Visibility | **30 m** |
| Colour temperature | **5700 K** |
| Nominal voltage AC | **210-250 V** |
| Light source | **LED** |
| Maximum light power | **2 W** |
| Active power | **6.3 W** |
| LED lifetime | **50000 h** |
| Minimum temperature | **+5 °C** |
| Maximum temperature | **+40 °C** |
| Battery | **LiFePO4/C (LN) 6.4V 1.5-1.6Ah** |
| Warranty (body, electronics, light source) | **36 months** |
| Net dimensions **L x W x H** [±2 mm] | **357 mm x 91 mm x 240 mm** |




* Some of mounting methods are possible only with additonal accessory dedicated for that product.