

PRIMO PP 30D 180 M DATA2 M

TM-PP.30D.BD03M



No: 1725



No: 4329/2021
Valid until:
19.05.2026



No:
B_BK_60112_0427_2024
Valid until:
24.01.2030




No: 1725



No: DC-UAE-
0180
Valid until:
19.05.2026



No: 1725



No: DIT_001



No: V1.0



Producer **TM Technologie**

Category **emergency luminaires**

Application **evacuation route direction**

Family **PRIMO PP**

Colour structure **gloss**

Version **DATA2**

Operating mode **M**

Duration time **3 h**

Protection degree **IP20**

Impact protection degree **IK07**

Appliance classes **I**

Material **stainless steel**

Installation method* **ceiling**

Adapted to use a pictogram **yes**

Pictogram included **yes**

Pictogram dimensions **300x150 mm**

Evacuation sign dimensions **300x150 mm**

Pictogram type **sticker**

Graphic number **K3**

Luminous flux **>500 cd/m²**

Visibility **30 m**

Colour temperature **5700 K**

Nominal voltage AC **210-250 V**

Light source **LED**

Maximum light power **2 W**

LED lifetime **50000 h**

Minimum temperature **+5 °C**

Maximum temperature **+40 °C**

Battery **LiFePO4/C 6.4V 1.5Ah**

Warranty (body, electronics, light source) **60 months**

Net dimensions **L x W x H [±2 mm]** **357 mm x 91 mm x 240 mm**

