TM TECHNOLOGIE

PRIMO PP 30D 180 M DATA2 W
TM-PP.30D.BD03W

Click on the selected icon to download the file:

No: 1726 | No: 6077/2026 Valid until: 19.05.2031 | No: B_BK_60112_0427_2024 Valid until: 24.01.2030 | No: 1726 | No: DC-UAE-0374 Valid until: 19.05.2031 | No: 1726 | No: DIT.V1.01 | No: V1.0

Producer	**TM TECHNOLOGIE**
Category	**emergency luminaires**
Application	**evacuation route direction**
Family	**PRIMO PP**
Colour	**white**
Colour - RAL	**RAL9003**
Colour structure	**painted**
Version	**DATA2**
Operating mode	**M**
Duration time	**3 h**
Protection degree	**IP20**
Impact protection degree	**IK07**
Appliance classes	**I**
Material	**steel**
Installation method*	**ceiling**
Adapted to use a pictogram	**yes**
Pictogram included	**yes**
Pictogram dimensions	**300x150 mm**
Evacuation sign dimensions	**300x150 mm**
Pictogram type	**sticker**
Graphic number	**K3**
Luminous flux	**>500 cd/m²**
Visibility	**30 m**
Colour temperature	**5700 K**
Nominal voltage AC	**210-250 V**
Light source	**LED**
Maximum light power	**2 W**
Active power	**6.3 W**
LED lifetime	**50000 h**
Minimum temperature	**+5 °C**
Maximum temperature	**+40 °C**
Battery	**LiFePO4/C (LN) 6.4V 1.5-1.6Ah**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **L x W x H** [±2 mm]	**357 mm x 91 mm x 240 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.