PRIMO Q 30E CBM W
TM-PQ.3ECBM000W

Click on the selected icon to download the file:

No: 2926 No: 2926 No: 2926 No: DIT.V2.03 No: V2.3



Producer	**TM TECHNOLOGIE**
Application	**evacuation route direction**
Family	**PRIMO Q**
Colour	**white**
Colour - RAL	**RAL9003**
Version	**CBM - Central addressable modulation battery**
Operating mode	**CB**
Protection degree	**IP20**
Impact protection degree	**IK05**
Appliance classes	**I**
Material	**steel**
Installation method*	**surface, suspended, ceiling**
Luminous flux	**>150 cd/m²**
Light source	**LED**
Maximum light power	**4.5 W**
Active power	*** W**
LED lifetime	**50000 h**
Nominal voltage AC	**210-250 V**
Nominal voltage DC	**186-254 V**
Colour temperature	**5700 K**
Minimum temperature	**-15 °C**
Maximum temperature	**+55 °C**
Battery	**-**
Power Factor Correction	**0,56**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **L x W x H** [±2 mm]	**399 mm x 399 mm x 192 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.