PRIMO Q 30E 180 M DALI-2 W
TM-PQ.3EDLM800W

Click on the selected icon to download the file:

No: 2926 No: 2926 No: 10344 No: 2926 No: DIT.V2.03 No: V2.3



Producer	**TM TECHNOLOGIE**
Category	**emergency luminaires**
Application	**evacuation route direction**
Family	**PRIMO Q**
Colour	**white**
Colour - RAL	**RAL9003**
Colour structure	**painted**
Version	**DALI2**
Operating mode	**M**
Duration time	**3 h**
Protection degree	**IP20**
Impact protection degree	**IK05**
Appliance classes	**I**
Material	**steel**
Installation method*	**surface, suspended, ceiling**
Adapted to use a pictogram	**yes**
Pictogram dimensions	**317x179 mm**
Evacuation sign dimensions	**300x150 mm**
Pictogram type	**foil**
Luminous flux	**>150 cd/m²**
Visibility	**30 m**
Colour temperature	**5700 K**
Nominal voltage AC	**210-250 V**
Nominal voltage DC	**- V**
Light source	**LED**
Maximum light power	**2.1 W**
Active power	**3.0 W**
LED lifetime	**50000 h**
Minimum temperature	**+5 °C**
Maximum temperature	**+40 °C**
Battery	**LiFePO4/C (LN) 3.2V 1.5-1.6Ah**
DALI type	**A**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **L x W x H** [±2 mm]	**399 mm x 399 mm x 192 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.