

# PRIMO Q 30E 180 M ST W TM-PQ.3ESTM800W

Click on the selected icon to download the file:



No: 2925



No: 2925



No: 2925



No: DIT\_001



No: V2.3



Producer	<b>TM Technologie</b>
Application	<b>evacuation route direction</b>
Family	<b>PRIMO Q</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Version	<b>standard</b>
Operating mode	<b>M</b>
Duration time	<b>3 h</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK05</b>
Appliance classes	<b>I</b>
Material	<b>steel</b>
Installation method*	<b>surface, suspended, ceiling</b>
Luminous flux	<b>&gt;150 cd/m<sup>2</sup></b>
Light source	<b>LED</b>
Maximum light power	<b>2.1 W</b>
Active power	<b>3.01 W</b>
Nominal voltage AC	<b>210-250 V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>+5 °C</b>
Maximum temperature	<b>+40 °C</b>
Battery	<b>LiFePO4/C (LN) 3.2V 1.5-1.6Ah</b>
Warranty (body, electronics, light source)	<b>24 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>399 mm x 399 mm x 192 mm</b>

