

PRIMO Q 40E 180 M DALI-2 W TM-PQ.4EDLM800W

Click on the selected icon to download the file:



No: 2925



No: 2925



No: 10338



No: 2925




No: V1



No: V2,3



Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction
Family	PRIMO Q
Colour/Colour - RAL	white , RAL9003
Colour structure	painted
Version	DALI2
Operating mode	M
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK05
Appliance classes	I
Material	steel
Installation method*	surface, suspended, ceiling
Adapted to use a pictogram	yes
Pictogram dimensions	417x229 mm
Evacuation sign dimensions	400x200 mm
Pictogram type	foil
Luminous flux	>150 cd/m²
Visibility	40 m
Colour temperature	5700 K
Nominal voltage AC	210-250 V
Nominal voltage DC	- V
Light source	LED
Maximum light power	4.5 W
LED lifetime	50000 h
Minimum temperature	+5 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 3.2V 3.0-3.2Ah
DALI type	A
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	499 mm x 499 mm x 242 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.