PRIMO R C1 180 NM AT W
TM-PR.C1ATN800W

Click on the selected icon to download the file:

No: 0826

No: 4601/2022
Valid until:
21.03.2027

No: 88-128842

No:
B_BK_60112_0430_2024
Valid until:
24.01.2030

No: 0826

No: DC-UAE-
0206
Valid until:
21.03.2027


No: 0826

No: DIT.V1.01

No: V1.8



Producer	**TM TECHNOLOGIE**
Application	**escape route lighting**
Family	**PRIMO R**
Colour	**white**
Colour - RAL	**RAL9003**
Version	**autotest**
Operating mode	**NM**
Duration time	**3 h**
Protection degree	**IP20**
Impact protection degree	**IK05**
Appliance classes	**I**
Material	**steel**
Installation method*	**surface, wall, ceiling**
Luminous flux emergency	**137 lm**
Light source	**LED**
Maximum light power	**2.5 W**
Active power	**1.2 W**
LED lifetime	**50000 h**
Nominal voltage AC	**210-250 V**
Colour temperature	**5700 K**
Minimum temperature	**+10 °C**
Maximum temperature	**+35 °C**
Battery	**LiFePO4/C (LN) 3.2V 1.5-1.6Ah**
Warranty (body, electronics, light source)	**36 months**
Net dimensions **L x W x H** [±2 mm]	**136 mm x 36 mm x 131 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.