

# PRIMO R M1 60 NM DATA2 W TM-PR.M1BDN600W

Click on the selected icon to download the file:



No: 0825



No: 4601/2022  
Valid until:  
21.03.2027



No: 88-128842



No:  
B\_BK\_60112\_0430\_2024  
Valid until:  
24.01.2030



No: 0825



No: DC-UAE-0206  
Valid until:  
21.03.2027



No: 0825



No: V1



No: V1.7



Producer	<b>TM Technologie</b>
Application	<b>anti-panic lighting</b>
Family	<b>PRIMO R</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Version	<b>DATA2</b>
Operating mode	<b>NM</b>
Duration time	<b>1 h</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK05</b>
Appliance classes	<b>I</b>
Material	<b>steel</b>
Installation method*	<b>surface, ceiling</b>
Luminous flux emergency	<b>333 lm</b>
Light source	<b>LED</b>
Maximum light power	<b>2.5 W</b>
Active power	<b>1.2 W</b>
Nominal voltage AC	<b>210-250 V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>+10 °C</b>
Maximum temperature	<b>+35 °C</b>
Battery	<b>LiFePO4/C (LN) 3.2V 1.5-1.6Ah</b>
Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>136 mm x 36 mm x 131 mm</b>

