

PRIMO PPZ 30DS 180 M DATA2 W TM-PZ.30DSBD03W

Click on the selected icon to download the file:



No: 1725



No: 6077/2026
Valid until:
19.05.2031



No:
B_BK_60112_0427_2024
Valid until:
24.01.2030



No: 1725



No: DC-UAE-
0374
Valid until:
19.05.2031



No: 1725




No: DIT_001



No: V1.1



Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction
Family	PRIMO APZ
Colour/Colour - RAL	white , RAL9003
Colour structure	painted
Version	DATA2
Operating mode	M
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK07
Appliance classes	I
Material	steel
Installation method*	ceiling
Adapted to use a pictogram	yes
Pictogram included	yes
Pictogram dimensions	319x193 mm
Evacuation sign dimensions	300x150 mm
Pictogram type	foil
Graphic number	K3, D3
Luminous flux	>500 cd/m²
Visibility	30 m
Colour temperature	5700 K
Nominal voltage AC	210-250 V
Light source	LED
Maximum light power	2.1 W
LED lifetime	50000 h
Minimum temperature	+5 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 6.4V 3.0-3.2Ah
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	324 mm x 61 mm x 783 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.



3	6	13	-	-
3,5	6,5	15,5	-	-
4,5	5	17	-	-
5,5	3	15	-	-
5,5	3	13	-	-
7,5	4	12	-	-
E _{min} ≥ 0,5 lx				