

PRIMO PPZ 30DS CB W TM-PZ.30DSCB01W

Click on the selected icon to download the file:



No: 1725



No: 6077/2026
Valid until:
19.05.2031



No: B_BK_60112_0427_2024
Valid until:
24.01.2030



No: 1725



No: DC-UAE-0374
Valid until:
19.05.2031



No: 1725






No: V1.1



Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction
Family	PRIMO PPZ
Colour/Colour - RAL	white , RAL9003
Colour structure	painted
Version	CB - central battery
Operating mode	CB
Protection degree	IP20
Impact protection degree	IK07
Appliance classes	I
Material	steel
Installation method*	ceiling
Adapted to use a pictogram	yes
Pictogram included	yes
Pictogram dimensions	319x193 mm
Evacuation sign dimensions	300x150 mm
Pictogram type	foil
Graphic number	K3, D3
Luminous flux	>500 cd/m²
Visibility	30 m
Colour temperature	5700 K
Nominal voltage AC	210-250 V
Nominal voltage DC	186-254 V
Light source	LED
Maximum light power	2.1 W
LED lifetime	50000 h
Minimum temperature	-15 °C
Maximum temperature	+55 °C

Warranty (body, electronics, light source) **60 months**
Net dimensions **L x W x H [±2 mm]** **324 mm x 61 mm x 783 mm**





3	6	13	-	-
3,5	6,5	15,5	-	-
4,5	5	17	-	-
5,5	3	15	-	-
5,5	3	13	-	-
7,5	4	12	-	-
E _{min} ≥ 0,5 lx				