

# PRIMO PPZ 30DS CB W TM-PZ.30DSCB01W

Click on the selected icon to download the file:



No: 1725



No: 6077/2026  
Valid until:  
19.05.2031



No: B\_BK\_60112\_0427\_2024  
Valid until:  
24.01.2030



No: 1725



No: DC-UAE-0374  
Valid until:  
19.05.2031



No: 1725





No: V1.1



Producer	<b>TM Technologie</b>
Category	<b>emergency luminaires</b>
Application	<b>evacuation route direction</b>
Family	<b>PRIMO PPZ</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Colour structure	<b>painted</b>
Version	<b>CB - central battery</b>
Operating mode	<b>CB</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK07</b>
Appliance classes	<b>I</b>
Material	<b>steel</b>
Installation method*	<b>ceiling</b>
Adapted to use a pictogram	<b>yes</b>
Pictogram included	<b>yes</b>
Pictogram dimensions	<b>319x193 mm</b>
Evacuation sign dimensions	<b>300x150 mm</b>
Pictogram type	<b>foil</b>
Graphic number	<b>K3, D3</b>
Luminous flux	<b>&gt;500 cd/m<sup>2</sup></b>
Visibility	<b>30 m</b>
Colour temperature	<b>5700 K</b>
Nominal voltage AC	<b>210-250 V</b>
Nominal voltage DC	<b>186-254 V</b>
Light source	<b>LED</b>
Maximum light power	<b>2.1 W</b>
LED lifetime	<b>50000 h</b>
Minimum temperature	<b>-15 °C</b>
Maximum temperature	<b>+55 °C</b>

Warranty (body, electronics, light source) **60 months**  
Net dimensions **L x W x H [±2 mm]** **324 mm x 61 mm x 783 mm**





3	6	13	-	-
3,5	6,5	15,5	-	-
4,5	5	17	-	-
5,5	3	15	-	-
5,5	3	13	-	-
7,5	4	12	-	-
E <sub>min</sub> ≥ 0,5 lx				