

# INDUST R 3D CB DALI-2 H

## TM-RP.D0CDO300H

Click on the selected icon to download the file:



No: 2625



No: 4956/2023  
Valid until:  
10.05.2028



No: 2625



No: 2016



No: 2625



No: V1.0



Producer **TM Technologie**  
Category **emergency luminaires**  
Application **evacuation route direction, tunnel lighting**

Family **INDUST R**

Colour structure **raw**

Version **CD - CB DALI2**

Operating mode **CB**

Protection degree **IP66, IP69**

Impact protection degree **IK08**

Appliance classes **I**

Material **stainless steel**

Installation method\* **surface, wall**

Adapted to use a pictogram **yes**

Pictogram dimensions **315, 6x324, 6 mm**

Evacuation sign dimensions **300x300 mm**

Pictogram type **foil**

Luminous flux **>200 cd/m<sup>2</sup>**

Visibility **60 m**

Colour temperature **5700 K**

Nominal voltage AC **220-240 V**

Nominal voltage DC **186-254 V**

Light source **LED**

Maximum light power **1.5 W**

LED lifetime **50000 h**

Minimum temperature **-25 °C**

Maximum temperature **+45 °C**

DALI type **A**

Warranty (body, electronics, light source) **60 months**

Net dimensions **L x W x H [±2 mm]** **384 mm x 141 mm x 356 mm**

