

INDUST R 1DF CB H

TM-RP.DFCB0100H

Click on the selected icon to download the file:



No: 2625



No: 4956/2023
Valid until:
10.05.2028




No: 2625



No: 2625




No: V1.0



Producer	TM TECHNOLOGIE
Category	emergency luminaires
Application	evacuation route direction, tunnel lighting
Family	INDUST R
Colour structure	raw
Version	CB - central battery
Operating mode	CB
Protection degree	IP66, IP69
Impact protection degree	IK08
Appliance classes	I
Material	stainless steel
Installation method*	surface, wall
Adapted to use a pictogram	yes
Pictogram dimensions	315, 6X174, 6 mm
Evacuation sign dimensions	300x150 mm
Pictogram type	foil
Luminous flux	>200 cd/m²
Visibility	30 m
Colour temperature	5700 K
Nominal voltage AC	220-240 V
Nominal voltage DC	186-254 V
Light source	LED
Maximum light power	0.8 W
LED lifetime	50000 h
Minimum temperature	-25 °C
Maximum temperature	+45 °C

Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	384 mm x 121 mm x 246 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.