

ONTEC S20 M1 60 MAT W IP65 TM-S2.M1ATM160W

Click on the selected icon to download the file:



No: 1625



No: 4302/2021
Valid until:
15.04.2026



No: 88-129369



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No:
2291559.02.UAE
Valid until:
05.11.2026



No: 1625



No: DIT_003




No: V3.0



Producer	TM Technologie
Application	anti-panic lighting
Family	ONTEC S20
Colour/Colour - RAL	white , RAL9003
Version	autotest
Operating mode	M
Duration time	1 h
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux	>2 cd/m²
Luminous flux emergency	371 lm
Light source	LED
Maximum light power	3 W
Active power	3.57 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah
Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	227 mm x 40 mm x 120 mm





2,5	3,5	8	3,5	8
3	3,5	9,5	3,5	9,5
4	4,5	11,5	4,5	11,5
5	5	13	5	13
6	5	15	5	15
7	5	16,5	5	16,5
8	5,5	18	5,5	18
9	5,5	19	5,5	19
10	5,5	20	5,5	20

$E_{min} \geq 0,5 \text{ lx}$