

ONTEC S20 M2 180 M AT W IP65 TM-S2.M2ATM360W

Click on the selected icon to download the file:



No: 1625



No: 6074/2026
Valid until:
15.04.2031



No: 88-129369



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No:
2291559.02.UAE
Valid until:
05.11.2026



No: 1625




No: V2



No: V3.0



Producer	TM Technologie
Application	anti-panic lighting, evacuation route direction
Family	ONTEC S20
Colour/Colour - RAL	white , RAL9003
Version	autotest
Operating mode	M
Duration time	3 h
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux	>2 cd/m²
Luminous flux emergency	309 lm
Light source	LED
Maximum light power	2.5 W
Active power	4.7 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 2x3.2V 1.5-1.6Ah
Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	227 mm x 40 mm x 120 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	3,5	8	3,5	8
3	3,5	9	3,5	9
4	4,5	11	4,5	11
5	5	12,5	5	12,5
6	5	14,5	5	14,5
7	5	16	5	16
8	5,5	17	5,5	17
9	5,5	18	5,5	18
10	5	19	5	19

$E_{min} \geq 0,5 \text{ lx}$