

ONTEC S20 M2 180 M AT W IP65 TM-S2.M2ATM360W

Click on the selected icon to download the file:



No: 1625



No: 6074/2026
Valid until:
15.04.2031



No: 88-129369



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No:
2291559.02.UAE
Valid until:
05.11.2026



No: 1625




No: V2



No: V3.0



| | |
|--|--|
| Producer | TM Technologie |
| Application | anti-panic lighting, evacuation route direction |
| Family | ONTEC S20 |
| Colour/Colour - RAL | white , RAL9003 |
| Version | autotest |
| Operating mode | M |
| Duration time | 3 h |
| Protection degree | IP65 |
| Impact protection degree | IK08 |
| Appliance classes | II |
| Material | plastic |
| Installation method* | surface, flush-mounted, suspended, wall, ceiling, at an angle |
| Luminous flux | >2 cd/m² |
| Luminous flux emergency | 309 lm |
| Light source | LED |
| Maximum light power | 2.5 W |
| Active power | 4.7 W |
| Nominal voltage AC | 210-250 V |
| LED lifetime | 50000 h |
| Colour temperature | 5700 K |
| Minimum temperature | + 0 °C |
| Maximum temperature | +40 °C |
| Battery | LiFePO4/C (LN) 2x3.2V 1.5-1.6Ah |
| Warranty (body, electronics, light source) | 36 months |
| Net dimensions L x W x H [±2 mm] | 227 mm x 40 mm x 120 mm |



* Some of mounting methods are possible only with additional accessory dedicated for that product.



| | | | | |
|-----|-----|------|-----|------|
| 2,5 | 3,5 | 8 | 3,5 | 8 |
| 3 | 3,5 | 9 | 3,5 | 9 |
| 4 | 4,5 | 11 | 4,5 | 11 |
| 5 | 5 | 12,5 | 5 | 12,5 |
| 6 | 5 | 14,5 | 5 | 14,5 |
| 7 | 5 | 16 | 5 | 16 |
| 8 | 5,5 | 17 | 5,5 | 17 |
| 9 | 5,5 | 18 | 5,5 | 18 |
| 10 | 5 | 19 | 5 | 19 |

$E_{min} \geq 0,5 \text{ lx}$