

# ONTEC S20 M1U 60/180 NM ST W IP44 TM-S2.MUSTN040W

Click on the selected icon to download the file:



No: 1625



No: 6074/2026  
Valid until:  
15.04.2031



No: 88-129369



No:  
B\_BK\_60112\_0426\_2024  
Valid until:  
24.01.2030



No: 1625



No:  
2291559.02.UAE  
Valid until:  
05.11.2026



No: 1625



No: V1



No: V3.0



Producer	<b>TM Technologie</b>
Application	<b>anti-panic lighting, evacuation route direction</b>
Family	<b>ONTEC S20</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Version	<b>standard</b>
Operating mode	<b>NM</b>
Duration time	<b>1/3 h</b>
Protection degree	<b>IP44</b>
Impact protection degree	<b>IK08</b>
Appliance classes	<b>II</b>
Material	<b>plastic</b>
Installation method*	<b>surface, flush-mounted, suspended, wall, ceiling, at an angle</b>
Luminous flux	<b>&gt;2 cd/m<sup>2</sup></b>
Luminous flux emergency	<b>371(1h);154(3h) lm</b>
Light source	<b>LED</b>
Maximum light power	<b>3 W</b>
Active power	<b>1.95 W</b>
Nominal voltage AC	<b>210-250 V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>+ 0 °C</b>
Maximum temperature	<b>+40 °C</b>
Battery	<b>LiFePO4/C (LN) 3.2V 1.5-1.6Ah</b>
Warranty (body, electronics, light source)	<b>24 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>227 mm x 40 mm x 120 mm</b>





*60				
2,5	3,5	8	3,5	8
3	3,5	9,5	3,5	9,5
4	4,5	11,5	4,5	11,5
5	5	13	5	13
6	5	15	5	15
7	5	16,5	5	16,5
8	5,5	18	5,5	18
9	5,5	19	5,5	19
10	5,5	20	5,5	20
*180				
2,5	3	7	3	7
3	3,5	8	3,5	8
4	4	9,5	4	9,5
5	4	11	4	11
6	3,5	12,5	3,5	12,5
7	3,5	13,5	3,5	13,5
8	3,5	14	3,5	14
9	3	14,5	3	14,5
10	2	15	2	15
Emin ≥ 0,5 lx				