

ONTEC S20 M1U 60/180 NM ST W IP44 TM-S2.MUSTN040W

Click on the selected icon to download the file:



No: 1625



No: 6074/2026
Valid until:
15.04.2031



No: 88-129369



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No:
2291559.02.UAE
Valid until:
05.11.2026



No: 1625




No: V1



No: V3.0



Producer	TM Technologie
Application	anti-panic lighting, evacuation route direction
Family	ONTEC S20
Colour/Colour - RAL	white , RAL9003
Version	standard
Operating mode	NM
Duration time	1/3 h
Protection degree	IP44
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux	>2 cd/m²
Luminous flux emergency	371(1h);154(3h) lm
Light source	LED
Maximum light power	3 W
Active power	2.0 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah
Warranty (body, electronics, light source)	24 months
Net dimensions L x W x H [±2 mm]	227 mm x 40 mm x 120 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.



*60				
2,5	3,5	8	3,5	8
3	3,5	9,5	3,5	9,5
4	4,5	11,5	4,5	11,5
5	5	13	5	13
6	5	15	5	15
7	5	16,5	5	16,5
8	5,5	18	5,5	18
9	5,5	19	5,5	19
10	5,5	20	5,5	20
*180				
2,5	3	7	3	7
3	3,5	8	3,5	8
4	4	9,5	4	9,5
5	4	11	4	11
6	3,5	12,5	3,5	12,5
7	3,5	13,5	3,5	13,5
8	3,5	14	3,5	14
9	3	14,5	3	14,5
10	2	15	2	15
Emin ≥ 0,5 lx				