

# ONTEC S20 M2X CBM W IP65 TM-S2.MXCBM060W

Click on the selected icon to download the file:



No: 1625



No: 6074/2026  
Valid until:  
15.04.2031



No: 88-144520  
Valid until:  
28.02.2027



No:  
B\_BK\_60112\_0426\_2024  
Valid until:  
24.01.2030



No: 1625



No:  
2291559.01.UAE  
Valid until:  
28.10.2026



No: 1625




No: V2



No: V3.0



Producer	<b>TM Technologie</b>
Application	<b>anti-panic lighting, evacuation route direction</b>
Family	<b>ONTEC S20</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Version	<b>CBM - Central addressable modulation battery</b>
Operating mode	<b>CB</b>
Protection degree	<b>IP65</b>
Impact protection degree	<b>IK08</b>
Appliance classes	<b>II</b>
Material	<b>plastic</b>
Installation method*	<b>surface, flush-mounted, suspended, wall, ceiling, at an angle</b>
Luminous flux	<b>&gt;2 cd/m<sup>2</sup></b>
Luminous flux emergency	<b>154(L);309(H) lm</b>
Light source	<b>LED</b>
Maximum light power	<b>2.5 W</b>
Active power	<b>4.4 W</b>
Nominal voltage AC	<b>210-250 V</b>
Nominal voltage DC	<b>186-254 V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>-15 °C</b>
Maximum temperature	<b>+55 °C</b>
Battery	<b>-</b>
Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>227 mm x 40 mm x 120 mm</b>



\* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	3,5	8	3,5	8
3	3,5	9	3,5	9
4	4,5	11	4,5	11
5	5	12,5	5	12,5
6	5	14,5	5	14,5
7	5	16	5	16
8	5,5	17	5,5	17
9	5,5	18	5,5	18
10	5	19	5	19

$E_{min} \geq 0,5 \text{ lx}$