

ONTEC S20 M1X 60/180 M/NM DALI-2 B IP65 TM-S2.MXDLX060B

Click on the selected icon to download the file:



No: 1625



No: 4302/2021
Valid until:
15.04.2026



No: B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No: 7089



No: 1625



No: V3.0



Dii Certificate

<https://www.dali-alliance.org/products/7089/vip-s>

Producer

TM Technologie

Category

emergency luminaires

Application

anti-panic lighting, evacuation route direction

Family

ONTEC S20

Colour/Colour - RAL

black , RAL9005

Colour structure

smooth, gloss

Version

DALI2

Operating mode

M/NM

Duration time

1/3 h

Protection degree

IP65

Impact protection degree

IK08

Appliance classes

II

Material

plastic

Installation method*

surface, flush-mounted, suspended, wall, ceiling, at an angle

Adapted to use a pictogram

yes

Pictogram included

yes

Pictogram dimensions

100x100 mm

Pictogram type

foil

Graphic number

K5

Luminous flux

>2 cd/m²

Visibility

20 m

Colour temperature

5700 K

Nominal voltage AC

210-250 V

Nominal voltage DC

- V

Light source

LED

Maximum light power

3 W

LED lifetime

50000 h

Minimum temperature

+ 0 °C

Maximum temperature

+40 °C

Battery

LiFePO4/C (LN) 3.2V 1.5-1.6Ah

DALI type


A


Warranty (body, electronics, light source)

60 months

Net dimensions L x W x H [±2 mm]

227 mm x 40 mm x 120 mm





*60				
2,5	3,5	8	3,5	8
3	3,5	9,5	3,5	9,5
4	4,5	11,5	4,5	11,5
5	5	13	5	13
6	5	15	5	15
7	5	16,5	5	16,5
8	5,5	18	5,5	18
9	5,5	19	5,5	19
10	5,5	20	5,5	20
*180				
2,5	3	7	3	7
3	3,5	8	3,5	8
4	4	9,5	4	9,5
5	4	11	4	11
6	3,5	12,5	3,5	12,5
7	3,5	13,5	3,5	13,5
8	3,5	14	3,5	14
9	3	14,5	3	14,5
10	2	15	2	15
Emin ≥ 0,5 lx				