

# ONTEC S30 C2 CB W IP65

## TM-S3.C2CB0060W

Click on the selected icon to download the file:



No: 1625



No: 4302/2021  
Valid until:  
15.04.2026



No: 88-146912  
Valid until:  
24.09.2029



No:  
B\_BK\_60112\_0426\_2024  
Valid until:  
24.01.2030



No: 1625



No: 2291560.01-  
UAE  
Valid until:  
08.10.2026



No: 1625




No: V3.0



Producer	<b>TM Technologie</b>
Application	<b>escape route lighting</b>
Family	<b>ONTEC S30</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Version	<b>CB - central battery</b>
Operating mode	<b>CB</b>
Protection degree	<b>IP65</b>
Impact protection degree	<b>IK08</b>
Appliance classes	<b>II</b>
Material	<b>plastic</b>
Installation method*	<b>surface, flush-mounted, suspended, wall, ceiling, at an angle</b>
Luminous flux emergency	<b>533 lm</b>
Light source	<b>LED</b>
Maximum light power	<b>5.1 W</b>
Active power	<b>6.9 W</b>
Nominal voltage AC	<b>210-250 V</b>
Nominal voltage DC	<b>186-254 V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>-25 °C</b>
Maximum temperature	<b>+55 °C</b>

Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>327 mm x 40 mm x 170 mm</b>



\* Some of mounting methods are possible only with additional accessory dedicated for that product.