

ONTEC S30 C2 CB W IP65 TM-S3.C2CB0060W

Click on the selected icon to download the file:



No: 1625



No: 6074/2026
Valid until:
15.04.2031



No: 88-146912
Valid until:
24.09.2029



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No: 2291560.01-
UAE
Valid until:
08.10.2026



No: 1625




No: V3.0



Producer	TM Technologie
Application	escape route lighting
Family	ONTEC S30
Colour/Colour - RAL	white , RAL9003
Version	CB - central battery
Operating mode	CB
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux emergency	533 lm
Light source	LED
Maximum light power	5.1 W
Active power	6.9 W
Nominal voltage AC	210-250 V
Nominal voltage DC	186-254 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	-25 °C
Maximum temperature	+55 °C
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	327 mm x 40 mm x 170 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	8,5	19	8,5	19
3	9,5	21	9,5	21
4	11,5	26	11,5	26
5	13	31	13	31
6	13,5	34	13,5	34
7	12,5	36	12,5	36
8	11	36,5	11	36,5
9	8	36	8	36
10	6,5	35	6,5	35