

ONTEC S30 C5 60 NM AT W IP65 TM-S3.C5ATN160W

Click on the selected icon to download the file:



No: 1625



No: 6074/2026
Valid until:
15.04.2031



No: 88-133122



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No: 2279257.01-
UAE
Valid until:
15.12.2025



No: 1625



No: DIT_004



No: V3.0



Producer	TM Technologie
Application	escape route lighting
Family	ONTEC S30
Colour/Colour - RAL	white , RAL9003
Version	autotest
Operating mode	NM
Duration time	1 h
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux emergency	1247 lm
Light source	LED
Maximum light power	5.8 W
Active power	2.27 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C (LN) 6.4V 3.0-3.2Ah
Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	327 mm x 40 mm x 170 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.



8	20	48	-	-
9	21	52	-	-
10	21	55	-	-
11	19	58	-	-
12	17	59	-	-
13	14	59	-	-
14	12	59	-	-
15	11	58	-	-
16	9	55	-	-
17	7	52	-	-
18	6	45	-	-
19	6	40	-	-
20	4	35	-	-

$E_{min} \geq 1 \text{ lx}$