

ONTEC S30 C5 180 NM AT W IP65 TM-S3.C5ATN360W

Click on the selected icon to download the file:



No: 1625



No: 6074/2026
Valid until:
15.04.2031



No: 88-133122



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No: 2279257.01-
UAE
Valid until:
15.12.2025



No: 1625



No: V2



No: V3.0



| | |
|--|--|
| Producer | TM TECHNOLOGIE |
| Application | escape route lighting |
| Family | ONTEC S30 |
| Colour/Colour - RAL | white , RAL9003 |
| Version | autotest |
| Operating mode | NM |
| Duration time | 3 h |
| Protection degree | IP65 |
| Impact protection degree | IK08 |
| Appliance classes | II |
| Material | plastic |
| Installation method* | surface, flush-mounted, suspended, wall, ceiling, at an angle |
| Luminous flux emergency | 1134 lm |
| Light source | LED |
| Maximum light power | 5.8 W |
| Active power | 4.0 W |
| Nominal voltage AC | 210-250 V |
| LED lifetime | 50000 h |
| Colour temperature | 5700 K |
| Minimum temperature | + 0 °C |
| Maximum temperature | +35 °C |
| Battery | LiFePO4/C (LN) 2x6.4V 3.0-3.2Ah |
| Warranty (body, electronics, light source) | 36 months |
| Net dimensions L x W x H [±2 mm] | 327 mm x 40 mm x 170 mm |



* Some of mounting methods are possible only with additional accessory dedicated for that product.



| | | | | |
|----|------|----|---|---|
| 8 | 19,5 | 47 | - | - |
| 9 | 20 | 51 | - | - |
| 10 | 18,5 | 54 | - | - |
| 11 | 17 | 55 | - | - |
| 12 | 15 | 57 | - | - |
| 13 | 12,5 | 56 | - | - |
| 14 | 11 | 55 | - | - |
| 15 | 9 | 53 | - | - |
| 16 | 7 | 50 | - | - |
| 17 | 5 | 45 | - | - |
| 18 | 4,5 | 40 | - | - |
| 19 | 4 | 35 | - | - |
| 20 | 3,5 | 30 | - | - |

$E_{min} \geq 1 \text{ lx}$