

ONTEC S30 F2 180 NM DATA2 W IP65 TM-S3.F2DDN360W



No: 1625



No: 4302/2021
Valid until:
15.04.2026



No: 88-133122



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No: 2279257.01-
UAE
Valid until:
15.12.2025



No: 1625



No: DIT_004




No: V3.0



Producer	TM Technologie
Application	escape route lighting
Family	ONTEC S30
Colour/Colour - RAL	white , RAL9003
Version	DATA2
Operating mode	NM
Duration time	3 h
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux emergency	554 lm
Light source	LED
Maximum light power	5.1 W
Active power	1.6 W
Nominal voltage AC	210-250 V
Nominal voltage DC	- V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 2x3.2V 3.0-3.2Ah
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	327 mm x 40 mm x 170 mm





8	12	29	-	-
9	12,5	31	-	-
10	13	32	-	-
11	13,5	34	-	-
12	14	35	-	-
13	14,5	36	-	-
14	14,5	37	-	-
15	15	38	-	-
16	15	39	-	-
17	15,5	40	-	-
18	15,5	40,5	-	-
19	16	41	-	-
20	16	42	-	-

$E_{min} \geq 1 \text{ lx}$