

ONTEC S30 F2 180 NM DATA2 W IP65 TM-S3.F2DDN360W

Click on the selected icon to download the file:



No: 1625



No: 6074/2026
Valid until:
15.04.2031



No: 88-133122



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No: 2279257.01-
UAE
Valid until:
15.12.2025



No: 1625



No: DIT_004





No: V3.0



Producer	TM Technologie
Application	escape route lighting
Family	ONTEC S30
Colour/Colour - RAL	white , RAL9003
Version	DATA2
Operating mode	NM
Duration time	3 h
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux emergency	554 lm
Light source	LED
Maximum light power	5.1 W
Active power	1.6 W
Nominal voltage AC	210-250 V
Nominal voltage DC	- V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 2x3.2V 3.0-3.2Ah
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	327 mm x 40 mm x 170 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	6	13
3	6,5	14,5
4	7,5	17
5	8	19
6	8,5	21
7	9	22,5
8	9,5	24
9	10	25
10	10,5	26