

ONTEC S30 M1X 60/180 M/NM DATA2 B

TM-S3.MXDDX060B



No: 1625



No: 4302/2021
Valid until:
15.04.2026



No: 88-133122



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No: 2279257.01-
UAE
Valid until:
15.12.2025



No: 1625



No: DIT_004





No: V3.0



Producer **TM Technologie**
Application **anti-panic lighting, evacuation route direction**

Family **ONTEC S30**
Colour/Colour - RAL **black , RAL9005**
Version **DATA2**
Operating mode **M/NM**
Duration time **1/3 h**
Protection degree **IP65**
Impact protection degree **IK08**
Appliance classes **II**
Material **plastic**
Installation method* **surface, flush-mounted, suspended, wall, ceiling, at an angle**
Luminous flux **>2 cd/m²**
Luminous flux emergency **414(1h);184(3h) lm**
Light source **LED**
Maximum light power **3.1 W**
Active power **4.35 W**
Nominal voltage AC **210-250 V**
Nominal voltage DC **- V**
LED lifetime **50000 h**
Colour temperature **5700 K**
Minimum temperature **+ 0 °C**
Maximum temperature **+40 °C**
Battery **LiFePO4/C (LN) 3.2V 1.5-1.6Ah**
Warranty (body, electronics, light source) **60 months**
Net dimensions **L x W x H [±2 mm]** **327 mm x 40 mm x 170 mm**





*60				
2,5	4	10	4	10
3	4,5	11	4,5	11
4	5	13,5	5	13,5
5	5	15,5	5	15,5
6	5,5	17	5,5	17
7	5	18,5	5	18,5
8	5	19,5	5	19,5
9	5	20,5	5	20,5
10	5	21	5	21
*180				
2,5	3,5	8,5	3,5	8,5
3	3,5	9,5	3,5	9,5
4	4	11	4	11
5	4	12,5	4	12,5
6	3,5	13,5	3,5	13,5
7	3,5	14	3,5	14
8	3	15	3	15
9	2,5	15,5	2,5	15,5
10	2,5	15,5	2,5	15,5
E _{min} ≥ 0,5 lx				