

ONTEC S30 M1X 60/180 M/NM DATA2 B TM-S3.MXDDX060B

Click on the selected icon to download the file:



No: 1625



No: 6074/2026
Valid until:
15.04.2031



No: 88-133122



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1625



No: 2279257.01-
UAE
Valid until:
15.12.2025



No: 1625



No: V2




No: V3.0



Producer	TM TECHNOLOGIE
Application	anti-panic lighting, evacuation route direction
Family	ONTEC S30
Colour/Colour - RAL	black , RAL9005
Version	DATA2
Operating mode	M/NM
Duration time	1/3 h
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux	>2 cd/m²
Luminous flux emergency	414(1h);184(3h) lm
Light source	LED
Maximum light power	3.1 W
Active power	3.6 W
Nominal voltage AC	210-250 V
Nominal voltage DC	- V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	327 mm x 40 mm x 170 mm





*60				
2,5	4	10	4	10
3	4,5	11	4,5	11
4	5	13,5	5	13,5
5	5	15,5	5	15,5
6	5,5	17	5,5	17
7	5	18,5	5	18,5
8	5	19,5	5	19,5
9	5	20,5	5	20,5
10	5	21	5	21
*180				
2,5	3,5	8,5	3,5	8,5
3	3,5	9,5	3,5	9,5
4	4	11	4	11
5	4	12,5	4	12,5
6	3,5	13,5	3,5	13,5
7	3,5	14	3,5	14
8	3	15	3	15
9	2,5	15,5	2,5	15,5
10	2,5	15,5	2,5	15,5
E _{min} ≥ 0,5 lx				