

# ONTEC S30 W5 180 NM DATA2 RADIO W IP65 TM-S3.W5DRN360W

Click on the selected icon to download the file:



No: 1625



No: 6074/2026  
Valid until:  
15.04.2031



No: 88-133122



No:  
B\_BK\_60112\_0426\_2024  
Valid until:  
24.01.2030



No: 1625




No: 1625




No: V3.0

Producer	<b>TM Technologie</b>
Application	<b>escape route lighting</b>
Family	<b>ONTEC S30</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Version	<b>DATA2 RADIO</b>
Operating mode	<b>NM</b>
Duration time	<b>3 h</b>
Protection degree	<b>IP65</b>
Impact protection degree	<b>IK08</b>
Appliance classes	<b>II</b>
Material	<b>plastic</b>
Installation method*	<b>surface, flush-mounted, suspended, wall, ceiling, at an angle</b>
Luminous flux emergency	<b>1090 lm</b>
Light source	<b>LED</b>
Maximum light power	<b>5.8 W</b>
Active power	<b>4.01 W</b>
Nominal voltage AC	<b>210-250 V</b>
Nominal voltage DC	<b>- V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>+ 0 °C</b>
Maximum temperature	<b>+35 °C</b>
Battery	<b>LiFePO4/C (LN) 2x6.4V 3.0-3.2Ah</b>
Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>327 mm x 40 mm x 170 mm</b>



\* Some of mounting methods are possible only with additional accessory dedicated for that product.



8	19,5	47	-	-
9	20	51	-	-
10	18,5	54	-	-
11	17	55	-	-
12	15	57	-	-
13	12,5	56	-	-
14	11	55	-	-
15	9	53	-	-
16	7	50	-	-
17	5	45	-	-
18	4,5	40	-	-
19	4	35	-	-
20	3,5	30	-	-

$E_{min} \geq 1 \text{ lx}$