

PRIMO TRL M1 180 NM AT B TM-TL.M1ATN800B

Click on the selected icon to download the file:



No: 3225



No: 3225



No: 3225



No: V1





No: V1.3



Producer	TM TECHNOLOGIE
Family	PRIMO TRL
Colour/Colour - RAL	black , RAL9005
Version	autotest
Operating mode	NM
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK08
Appliance classes	I
Material	steel
Installation method*	ceiling, surface
Luminous flux emergency	326 lm
Light source	LED
Maximum light power	2.5 W
Active power	1.6 W
Nominal voltage AC	210-250 V
Nominal voltage DC	- V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+ 35 °C
Battery	LiFePO4/C (LN) 3.2V 3.0-3.2Ah

Warranty (body, electronics, light source) **36 months**
 Net dimensions **L x W x H** [±2 mm] **350 mm x 50 mm x 89 mm**



h	a	b	c	d
2,5	3,5	9	3,5	9
3	4,5	10	4,5	10
4	5	12,5	5	12,5
5	5,5	14,5	5,5	14,5
6	5	16,5	5	16,5
7	4,5	18	4,5	18
8	4,5	19	4,5	19
9	4	20	4	20
10	4	20	4	20

E_{min} ≥ 0,5 lx

* Some of mounting methods are possible only with additional accessory dedicated for that product.