

PRIMO TRL M1 180 NM DALI W TM-TL.M1DAN800W

Click on the selected icon to download the file:



No: 3225



No: 3225



No: 1955



No: 3225



No: DIT_001



No: V1.3



DiiA Certificate

<https://www.dali-alliance.org/products/1955/vip-rs>

Producer

TM Technologie

Category

emergency luminaire

Family

PRIMO TRL

Colour/Colour - RAL

white , RAL9003

Version

DALI

Operating mode

NM

Duration time

3 h

Protection degree

IP20

Impact protection degree

IK08

Appliance classes

I

Material

steel

Colour structure

painted

Installation method*

ceiling, surface

Luminous flux emergency

326 lm

Nominal voltage AC

210-250 V

Nominal voltage DC

- V

Light source

LED

Maximum light power

2.5 W

LED lifetime

50000 h

Colour temperature

5700 K

Minimum temperature

+ 0 °C

Maximum temperature

+ 35 °C

Battery

LiFePO4/C (LN) 6.4V 1.5-1.6Ah

DALI type







D

Warranty (body, electronics, light source)

60 months

Net dimensions **L x W x H** [±2 mm]

350 mm x 50 mm x 89 mm



| | | | | |
|-----|-----|------|-----|------|
| 2,5 | 3,5 | 9 | 3,5 | 9 |
| 3 | 4,5 | 10 | 4,5 | 10 |
| 4 | 5 | 12,5 | 5 | 12,5 |
| 5 | 5,5 | 14,5 | 5,5 | 14,5 |
| 6 | 5 | 16,5 | 5 | 16,5 |
| 7 | 4,5 | 18 | 4,5 | 18 |
| 8 | 4,5 | 19 | 4,5 | 19 |
| 9 | 4 | 20 | 4 | 20 |
| 10 | 4 | 20 | 4 | 20 |

Emin ≥ 0,5 lx

* Some of mounting methods are possible only with additional accessory dedicated for that product.