

# PRIMO TRL M1 180 NM DALI B + ADAPTER TM-TL.M1DAN80SB

Click on the selected icon to download the file:



No: 3225



No: 3225



No: 1955



No: 3225



No: DIT\_001



No: V1.3



DiiA Certificate

<https://www.dali-alliance.org/products/1955/vip-rs>

Producer

**TM Technologie**

Category

**emergency luminaire**

Family

**PRIMO TRL**

Colour/Colour - RAL

**black , RAL9005**

Version

**DALI**

Operating mode

**NM**

Duration time

**3 h**

Protection degree

**IP20**

Impact protection degree

**IK08**

Appliance classes

**I**

Material

**steel**

Colour structure

**painted**

Installation method\*

**ceiling, surface**

Luminous flux emergency

**326 lm**

Nominal voltage AC

**210-250 V**

Nominal voltage DC

**- V**

Light source

**LED**

Maximum light power

**2.5 W**

LED lifetime

**50000 h**

Colour temperature

**5700 K**

Minimum temperature

**+ 0 °C**

Maximum temperature

**+ 35 °C**

Battery

**LiFePO4/C (LN) 6.4V 1.5-1.6Ah**

DALI type






**D**

Warranty (body, electronics, light source)

**60 months**

Net dimensions **L x W x H** [±2 mm]

**350 mm x 50 mm x 89 mm**



2,5	3,5	9	3,5	9
3	4,5	10	4,5	10
4	5	12,5	5	12,5
5	5,5	14,5	5,5	14,5
6	5	16,5	5	16,5
7	4,5	18	4,5	18
8	4,5	19	4,5	19
9	4	20	4	20
10	4	20	4	20

E<sub>min</sub> ≥ 0,5 lx

\* Some of mounting methods are possible only with additional accessory dedicated for that product.