

PRIMO TRL M1 180 NM DALI B + ADAPTER TM-TL.M1DAN80SB

Click on the selected icon to download the file:



No: 3225




No: 3225



No: 1955



No: 3225



No: DIT_001



No: V1.3






Producer **TM Technologie**
Category **emergency luminaires**

Family **PRIMO TRL**
Colour/Colour - RAL **black , RAL9005**

Version **DALI**
Operating mode **NM**
Duration time **3 h**
Protection degree **IP20**
Impact protection degree **IK08**
Appliance classes **I**
Material **steel**
Colour structure **painted**
Installation method* **ceiling, surface**

Luminous flux emergency **326 lm**
Nominal voltage AC **210-250 V**
Nominal voltage DC **- V**
Light source **LED**
Maximum light power **2.5 W**
LED lifetime **50000 h**
Colour temperature **5700 K**
Minimum temperature **+ 0 °C**
Maximum temperature **+ 35 °C**
Battery **LiFePO4/C (LN) 6.4V 1.5-1.6Ah**
DALI type **D**
Warranty (body, electronics, light source) **60 months**
Net dimensions **L x W x H [±2 mm]** **350 mm x 50 mm x 89 mm**



2,5	3,5	9	3,5	9
3	4,5	10	4,5	10
4	5	12,5	5	12,5
5	5,5	14,5	5,5	14,5
6	5	16,5	5	16,5
7	4,5	18	4,5	18
8	4,5	19	4,5	19
9	4	20	4	20
10	4	20	4	20

$E_{min} \geq 0,5 lx$

* Some of mounting methods are possible only with additional accessory dedicated for that product.