

# PRIMO TRL M1 180 NM DALI W + ADAPTER TM-TL.M1DAN80SW

Click on the selected icon to download the file:



No: 3225



No: 3225



No: 1955



No: 3225






No: DIT\_001



No: V1.3



Producer	<b>TM Technologie</b>
Category	<b>emergency luminaires</b>
Family	<b>PRIMO TRL</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Version	<b>DALI</b>
Operating mode	<b>NM</b>
Duration time	<b>3 h</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK08</b>
Appliance classes	<b>I</b>
Material	<b>steel</b>
Colour structure	<b>painted</b>
Installation method*	<b>ceiling, surface</b>
Luminous flux emergency	<b>326 lm</b>
Nominal voltage AC	<b>210-250 V</b>
Nominal voltage DC	<b>- V</b>
Light source	<b>LED</b>
Maximum light power	<b>2.5 W</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>+ 0 °C</b>
Maximum temperature	<b>+ 35 °C</b>
Battery	<b>LiFePO4/C (LN) 6.4V 1.5-1.6Ah</b>
DALI type	<b>D</b>
Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>350 mm x 50 mm x 89 mm</b>



2,5	3,5	9	3,5	9
3	4,5	10	4,5	10
4	5	12,5	5	12,5
5	5,5	14,5	5,5	14,5
6	5	16,5	5	16,5
7	4,5	18	4,5	18
8	4,5	19	4,5	19
9	4	20	4	20
10	4	20	4	20

$E_{min} \geq 0,5 lx$

\* Some of mounting methods are possible only with additional accessory dedicated for that product.