

# PRIMO TRL M1 180 NM DALI W + ADAPTER TM-TL.M1DAN80SW

Click on the selected icon to download the file:



No: 3225



No: 3225



No: 1955



No: 3225





No: V1



No: V1.3



|  |                                      |
|--|--------------------------------------|
| Producer                                   | <b>TM TECHNOLOGIE</b>                |
| Category                                   | <b>emergency luminaires</b>          |
| Family                                     | <b>PRIMO TRL</b>                     |
| Colour/Colour - RAL                        | <b>white , RAL9003</b>               |
| Version                                    | <b>DALI</b>                          |
| Operating mode                             | <b>NM</b>                            |
| Duration time                              | <b>3 h</b>                           |
| Protection degree                          | <b>IP20</b>                          |
| Impact protection degree                   | <b>IK08</b>                          |
| Appliance classes                          | <b>I</b>                             |
| Material                                   | <b>steel</b>                         |
| Colour structure                           | <b>painted</b>                       |
| Installation method*                       | <b>ceiling, surface</b>              |
| Luminous flux emergency                    | <b>326 lm</b>                        |
| Nominal voltage AC                         | <b>210-250 V</b>                     |
| Nominal voltage DC                         | <b>- V</b>                           |
| Light source                               | <b>LED</b>                           |
| Maximum light power                        | <b>2.5 W</b>                         |
| LED lifetime                               | <b>50000 h</b>                       |
| Colour temperature                         | <b>5700 K</b>                        |
| Minimum temperature                        | <b>+ 0 °C</b>                        |
| Maximum temperature                        | <b>+ 35 °C</b>                       |
| Battery                                    | <b>LiFePO4/C (LN) 6.4V 1.5-1.6Ah</b> |
| DALI type                                  | <b>D</b>                             |
| Warranty (body, electronics, light source) | <b>60 months</b>                     |
| Net dimensions <b>L x W x H</b> [±2 mm]    | <b>350 mm x 50 mm x 89 mm</b>        |



| h   | a   | b    | c   | d    |
|-----|-----|------|-----|------|
| 2,5 | 3,5 | 9    | 3,5 | 9    |
| 3   | 4,5 | 10   | 4,5 | 10   |
| 4   | 5   | 12,5 | 5   | 12,5 |
| 5   | 5,5 | 14,5 | 5,5 | 14,5 |
| 6   | 5   | 16,5 | 5   | 16,5 |
| 7   | 4,5 | 18   | 4,5 | 18   |
| 8   | 4,5 | 19   | 4,5 | 19   |
| 9   | 4   | 20   | 4   | 20   |
| 10  | 4   | 20   | 4   | 20   |

\* Some of mounting methods are possible only with additional accessory dedicated for that product.