
# PRIMO TRL M1 180 NM ST B
# TM-TL.M1STN800B


Click on the selected icon to download the file:

No: 3226 | No: 3226 | | No: 3226 | | No: DIT.V1.01 | No: V1.3



| | |
|---|---|
| Producer | **TM TECHNOLOGIE** |
| Family | **PRIMO TRL** |
| Colour | **black** |
| Colour - RAL | **RAL9005** |
| Version | **standard** |
| Operating mode | **NM** |
| Duration time | **3 h** |
| Protection degree | **IP20** |
| Impact protection degree | **IK08** |
| Appliance classes | **I** |
| Material | **steel** |
| Installation method* | **ceiling, surface** |
| Luminous flux emergency | **326 lm** |
| Light source | **LED** |
| Maximum light power | **2.5 W** |
| Active power | **1.6 W** |
| LED lifetime | **50000 h** |
| Nominal voltage AC | **210-250 V** |
| Nominal voltage DC | **- V** |
| Colour temperature | **5700 K** |
| Minimum temperature | **+ 0 °C** |
| Maximum temperature | **+ 35 °C** |
| Battery | **LiFePO4/C (LN) 3.2V 3.0-3.2Ah** |
| Warranty (body, electronics, light source) | **24 months** |
| Net dimensions **L x W x H** [±2 mm] | **350 mm x 50 mm x 89 mm** |



| h | a | b | c | d |
|---|---|---|---|---|
| 2,5 | 3,5 | 9 | 3,5 | 9 |
| 3 | 4,5 | 10 | 4,5 | 10 |
| 4 | 5 | 12,5 | 5 | 12,5 |
| 5 | 5,5 | 14,5 | 5,5 | 14,5 |
| 6 | 5 | 16,5 | 5 | 16,5 |
| 7 | 4,5 | 18 | 4,5 | 18 |
| 8 | 4,5 | 19 | 4,5 | 19 |
| 9 | 4 | 20 | 4 | 20 |
| 10 | 4 | 20 | 4 | 20 |

Emin ≥ 0,5 lx

* Some of mounting methods are possible only with additonal accessory dedicated for that product.