

PRIMO TRL M1 180 NM ST W TM-TL.M1STN800W

Click on the selected icon to download the file:



No: 3225



No: 3225



No: 3225






No: DIT_001



No: V1.3



| | |
|--|--------------------------------------|
| Producer | TM Technologie |
| Family | PRIMO TRL |
| Colour/Colour - RAL | white , RAL9003 |
| Version | standard |
| Operating mode | NM |
| Duration time | 3 h |
| Protection degree | IP20 |
| Impact protection degree | IK08 |
| Appliance classes | I |
| Material | steel |
| Installation method* | ceiling, surface |
| Luminous flux emergency | 326 lm |
| Light source | LED |
| Maximum light power | 2.5 W |
| Active power | 1.6 W |
| Nominal voltage AC | 210-250 V |
| Nominal voltage DC | - V |
| LED lifetime | 50000 h |
| Colour temperature | 5700 K |
| Minimum temperature | + 0 °C |
| Maximum temperature | + 35 °C |
| Battery | LiFePO4/C (LN) 3.2V 3.0-3.2Ah |
| Warranty (body, electronics, light source) | 24 months |
| Net dimensions L x W x H [±2 mm] | 350 mm x 50 mm x 89 mm |



| | | | | |
|-----|-----|------|-----|------|
| 2,5 | 3,5 | 9 | 3,5 | 9 |
| 3 | 4,5 | 10 | 4,5 | 10 |
| 4 | 5 | 12,5 | 5 | 12,5 |
| 5 | 5,5 | 14,5 | 5,5 | 14,5 |
| 6 | 5 | 16,5 | 5 | 16,5 |
| 7 | 4,5 | 18 | 4,5 | 18 |
| 8 | 4,5 | 19 | 4,5 | 19 |
| 9 | 4 | 20 | 4 | 20 |
| 10 | 4 | 20 | 4 | 20 |

E_{min} ≥ 0,5 lx

* Some of mounting methods are possible only with additional accessory dedicated for that product.