
PRIMO TRL M1 180 NM ST B + ADAPTER + FIXED ANGLE BRACKETS TM-TL.M1STN80KB


Click on the selected icon to download the file:


No: 3226 No: 3226 No: 3226 No: DIT.V1.01 No: V1.3



Producer	**TM TECHNOLOGIE**
Application	**anti-panic lighting**
Family	**PRIMO TRL**
Colour	**black**
Colour - RAL	**RAL9005**
Version	**standard**
Operating mode	**NM**
Duration time	**3 h**
Protection degree	**IP20**
Impact protection degree	**IK08**
Appliance classes	**I**
Material	**steel**
Installation method*	**ceiling, surface**
Luminous flux emergency	**326 lm**
Light source	**LED**
Maximum light power	**2.5 W**
Active power	**1.6 W**
LED lifetime	**50000 h**
Nominal voltage AC	**210-250 V**
Nominal voltage DC	**- V**
Colour temperature	**5700 K**
Minimum temperature	**+ 0 °C**
Maximum temperature	**+ 35 °C**
Battery	**LiFePO4/C (LN) 3.2V 3.0-3.2Ah**
Warranty (body, electronics, light source)	**24 months**
Net dimensions **L x W x H** [±2 mm]	**350 mm x 50 mm x 89 mm**







2,5	3,5	9	3,5	9
3	4,5	10	4,5	10
4	5	12,5	5	12,5
5	5,5	14,5	5,5	14,5
6	5	16,5	5	16,5
7	4,5	18	4,5	18
8	4,5	19	4,5	19
9	4	20	4	20
10	4	20	4	20

Emin ≥ 0,5 lx

* Some of mounting methods are possible only with additional accessory dedicated for that product.