

# PRIMO TRL M1 180 NM ST B + ADAPTER + FIXED ANGLE BRACKETS TM-TL.M1STN80KB

Click on the selected icon to download the file:



No: 3225



No: 3225



No: 3225





No: DIT\_001



No: V1.3



Producer	<b>TM Technologie</b>
Application	<b>anti-panic lighting</b>
Family	<b>PRIMO TRL</b>
Colour/Colour - RAL	<b>black , RAL9005</b>
Version	<b>standard</b>
Operating mode	<b>NM</b>
Duration time	<b>3 h</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK08</b>
Appliance classes	<b>I</b>
Material	<b>steel</b>
Installation method*	<b>ceiling, surface</b>
Luminous flux emergency	<b>326 lm</b>
Light source	<b>LED</b>
Maximum light power	<b>2.5 W</b>
Active power	<b>1.6 W</b>
Nominal voltage AC	<b>210-250 V</b>
Nominal voltage DC	<b>- V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>+ 0 °C</b>
Maximum temperature	<b>+ 35 °C</b>
Battery	<b>LiFePO4/C (LN) 3.2V 3.0-3.2Ah</b>
Warranty (body, electronics, light source)	<b>24 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>350 mm x 50 mm x 89 mm</b>



h	a	b	c	d
2,5	3,5	9	3,5	9
3	4,5	10	4,5	10
4	5	12,5	5	12,5
5	5,5	14,5	5,5	14,5
6	5	16,5	5	16,5
7	4,5	18	4,5	18
8	4,5	19	4,5	19
9	4	20	4	20
10	4	20	4	20

E<sub>min</sub> ≥ 0,5 lx

\* Some of mounting methods are possible only with additional accessory dedicated for that product.