

# INDUST TM 333D CB H TM-TM.D0CB0333H

Click on the selected icon to download the file:



No: 3025



No: 5047/2023  
Valid until:  
26.07.2028



No: 3025




No: 3025



No: V1.0



Producer	<b>TM TECHNOLOGIE</b>
Category	<b>emergency luminaires</b>
Application	<b>evacuation route direction</b>
Family	<b>INDUST TM</b>
Colour structure	<b>raw</b>
Version	<b>CB - central battery</b>
Operating mode	<b>CB</b>
Protection degree	<b>IP66, IP69</b>
Impact protection degree	<b>IK08</b>
Appliance classes	<b>I</b>
Material	<b>stainless steel</b>
Installation method*	<b>surface, wall</b>
Adapted to use a pictogram	<b>yes</b>
Pictogram dimensions	<b>353, 2x359, 2 mm</b>
Evacuation sign dimensions	<b>300x300 mm</b>
Pictogram type	<b>plexiglass PMMA</b>
Luminous flux	<b>&gt;200 cd/m<sup>2</sup></b>
Visibility	<b>60 m</b>
Colour temperature	<b>5700 K</b>
Nominal voltage AC	<b>220-240 V</b>
Nominal voltage DC	<b>186-254 V</b>
Light source	<b>LED</b>
Maximum light power	<b>1.5 W</b>
LED lifetime	<b>50000 h</b>
Minimum temperature	<b>-25 °C</b>
Maximum temperature	<b>+45 °C</b>
Battery	<b>-</b>
Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>581 mm x 319 mm x 1103 mm</b>



\* Some of mounting methods are possible only with additional accessory dedicated for that product.