

INDUST T 3DF CBM H TM-TP.DFCBM300H



No: 2625



No: 4956/2023
Valid until:
10.05.2028



No: 2625



No: 2625




No: DIT_004



No: V1.0



Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction, tunnel lighting
Family	INDUST T
Colour structure	raw
Version	CBM - Central addressable modulation battery
Operating mode	CB
Protection degree	IP66, IP69
Impact protection degree	IK08
Appliance classes	I
Material	stainless steel
Installation method*	surface, wall
Adapted to use a pictogram	yes
Pictogram dimensions	315, 6x324, 6 mm
Evacuation sign dimensions	300x300 mm
Pictogram type	foil
Luminous flux	>200 cd/m²
Visibility	60 m
Colour temperature	5700 K
Nominal voltage AC	220-240 V
Nominal voltage DC	186-254 V
Light source	LED
Maximum light power	1.6 W
LED lifetime	50000 h
Minimum temperature	-25 °C
Maximum temperature	+45 °C
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	604 mm x 274 mm x 394 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.